



Note: '()' correspond to the letters used in the product bulletin

Click [here](#) for the 3D model.

Dimensions

D	18mm +/-0.5mm
L	34.7mm +/-1mm
L1	41mm MIN
LL	40mm +/-2mm
F	1mm +/-0.03mm

Packaging Specifications

Packaging	Tray
-----------	------

General Information

Series	PEG236
Dielectric	Aluminum Electrolytic
Style	Axial
Description	Extremely High Ripple Axial Aluminum Electrolytic
RoHS	Yes
Lead	Wire Leads
Qualifications	AEC-Q200
AEC-Q200	Yes
Halogen Free	Yes
Component Weight	14 g

L1 is KEMET's recommendation for minimum distance between symmetrical Lead bend. Available only for Customer specific part numbers. Lead bend dimensions must be specified and confirmed per article.

Shelf Life	520 Weeks
------------	-----------

Specifications

Capacitance	1,800 uF
Capacitance Tolerance	-10/+30%
Voltage DC	25 VDC
Temperature Range	-40/+165°C
Rated Temperature	165°C
Life	9200 Hrs (Rated Voltage At 125C), 1000 Hrs (Rated Voltage At 165C)
Resistance	49 mOhms (100Hz 20C), 20 mOhms (100kHz 20C), 9.4 mOhms (5-100kHz 165C)
Ripple Current	20.39 Amps (5kHz 140C, With Heat Sink), 12.9 Amps (5kHz 155C, With Heat Sink), 5.8 Amps (5kHz 165C, With Heat Sink), 8 Amps (5kHz 140C), 2.3 Amps (>=5kHz 165C Max)
Leakage Current	139 uA (5min 20°C)

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)