



Click [here](#) for the 3D model.

### Dimensions

L	10mm +0.2/-0.5mm
H	10.5mm +0.1/-0.5mm
T	5mm +0.1/-0.5mm
S	7.5mm +/-0.4mm
H0	18.5mm +/-0.5mm
F	0.6mm +/-0.05mm

### Packaging Specifications

Packaging	Ammo, 360x340x59mm, Box
Packaging Quantity	1600

### General Information

Series	R76
Dielectric	Double Metallized Polypropylene
Style	Radial
Features	Automotive Grade, Pulse
RoHS	Yes
Lead	Wire Leads
Qualifications	AEC-Q200
AEC-Q200	Yes
Component Weight	0.969 g

### Specifications

Capacitance	2200 pF
Capacitance Tolerance	5%
Voltage AC	400 VAC
Voltage DC	1000 VDC
Temperature Range	-55/+110°C
Rated Temperature	85°C
Dissipation Factor	0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz
Insulation Resistance	100 GOhms
Max dV/dt	6000 V/us
Resistance	289.37 mOhms (100kHz)
Ripple Current	0.6 Amps (100kHz 85C), 13 Amps (Peak)
Inductance	8 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)