



Click [here](#) for the 3D model.

General Information

Series	SMD MIL BP PRF32535
Style	SMD Chip
Description	SMD, Low ESR, MIL-PRF-32535
RoHS	No
Prop 65	⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov
SCIP Number	d66873f5-e54d-410c-a0cf-ebf6fcf635b5
Termination	Solder Plated
Failure Rate	N/A
Qualifications	MIL-PRF-32535 T-Level
AEC-Q200	No
Shelf Life	78 Weeks
MSL	1

Dimensions

Chip Size	1812
L	4.52mm +/-0.3mm (0.178 in +/-0.012 in)
W	3.2mm +/-0.3mm (0.126 in +/-0.012 in)
T	2.79mm MAX (0.11 in MAX)
B	0.61mm +/-0.46mm (0.024 in +/-0.018 in)

Packaging Specifications

Packaging	Waffle
Packaging Quantity	42

Specifications

Capacitance	0.068 uF
Capacitance Tolerance	5%
Voltage DC	50 VDC
Dielectric Withstanding Voltage	125 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	BP
Dissipation Factor	0.25% 1 MHz 25C
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	14.71 GOhms

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)