



Click [here](#) for the 3D model.

Dimensions

| | |
|----|------------------|
| L | 32mm +0.3/-0.7mm |
| H | 20mm +0.1/-0.7mm |
| T | 11mm +0.2/-0.7mm |
| S | 27.5mm +/-0.4mm |
| LL | 30mm +5mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|-----|
| Packaging Quantity | 336 |
|--------------------|-----|

General Information

| | |
|---------------|---|
| Series | R76 |
| Dielectric | Double Metallized Polypropylene |
| Style | Radial |
| Features | Pulse |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Miscellaneous | Voltage Derating: 1.25%/C Above 85C (DC). |

Specifications

| | |
|-----------------------|--|
| Capacitance | 0.12 uF |
| Capacitance Tolerance | 5% |
| Voltage AC | 650 VAC |
| Voltage DC | 1600 VDC |
| Temperature Range | -55/+110°C |
| Rated Temperature | 85°C |
| Insulation Resistance | 100 GOhms |
| Max dV/dt | 2000 V/us |
| Resistance | 19.89 mOhms (100kHz) |
| Ripple Current | 5.658 Amps (100kHz 85C), 240 Amps (Peak) |
| Inductance | 18 nH |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)