



Click [here](#) for the 3D model.

Dimensions

Chip Size	1825
L	4.5mm +0.9/-0.3mm (0.177 in +0.035/-0.012 in)
W	6.4mm +0.6/-0.3mm (0.252 in +0.024/-0.012 in)
T	1.5mm +0.3mm (0.059 in +0.012 in)
B	0.5mm +0.6/-0.3mm (0.02 in +0.024/-0.012 in)

Packaging Specifications

Packaging	T&R, 178mm, Plastic Tape
Packaging Quantity	1100

General Information

Series	SMD Mil PRF55681
Style	SMD Chip
RoHS	No
Prop 65	WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov .
SCIP Number	6d5c4aea-4874-4964-b195-433620b8c028
Termination	Lead (SnPb)
Failure Rate	M (1%/1000 Hrs)
Testing and Reliability	MIL-PRF-55681
Qualifications	MIL-PRF-55681
AEC-Q200	No
Miscellaneous	Termination Description: SolderCoat 60-40.
Shelf Life	78 Weeks
MSL	1

Specifications

Capacitance	7500 pF
Capacitance Tolerance	5%
Voltage DC	100 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	BP

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)