
KEMET Part Number: CWR11MK685JBB



(T492D685J035BK4251)





Dimensions		
Footprint	7343	
L	7.3mm +/-0.3mm	
W	4.3mm +/-0.3mm	
Н	2.8mm +/-0.3mm	
Т	0.13mm REF	
S	1.3mm +/-0.3mm	
F	2.4mm +/-0.1mm	
В	0.5mm +/-0.15mm	
E	3.5mm REF	
G	3.5mm REF	
K	1mm MIN	
Р	0.5mm MIN	
R	1mm REF	
Х	0.1mm +/-0.1mm	

Packaging Specifications			
Packaging:	T&R, 178mm		
Packaging Quantity:	500		

General Information		
Series:	T492 CWR11	
Dielectric:	MnO2 Tantalum	
Style:	SMD Chip	
Description:	SMD, MnO2, Molded, Military Equivalent	
RoHS:	No	
Prop 65:	WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov.	
SCIP Number:	656db0b8-8445-4117-82f2-2f12e	764f0b1
Termination:	Solder Fused	
Qualifications:	MIL-PRF-55365/8, CWR11 Style	
AEC-Q200:	No	
Component Weight:	412.33 mg	
Notes:	Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K", "F" And "S".	
MSL:	1	

KEMET

a YAGEO company

Specifications		
Capacitance:	6.8 uF	
Capacitance Tolerance:	5%	
Voltage DC:	35 VDC (85C), 23.45 VDC (125C)	
Temperature Range:	-55/+125°C	
Rated Temperature:	85°C	
Dissipation Factor:	6% 120Hz 25C	
Failure Rate:	B (0.1%/1000 Hrs)	
Resistance:	1.3 Ohms (100kHz 25C)	
Leakage Current:	2.4 uA (5min 25°C)	
Testing and Reliability:	Surge Testing At -55C And +85C After Weibull	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)