



Click [here](#) for the 3D model.

Dimensions

| | |
|----|--------------------|
| L | 26.5mm +0.3/-0.5mm |
| H | 29.5mm +0.1/-0.5mm |
| T | 14.5mm +0.2/-0.5mm |
| S | 22.5mm +/-0.4mm |
| LL | 4mm +0.5mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|-----|
| Packaging Quantity | 264 |
|--------------------|-----|

General Information

| | |
|----------------|---|
| Series | R76 |
| Dielectric | Double Metallized Polypropylene |
| Style | Radial |
| Features | Automotive Grade, Pulse |
| RoHS | Yes |
| Lead | Cut |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Miscellaneous | Voltage Derating: 1.25%/C Above 85C (DC). |

Specifications

| | |
|-----------------------|--|
| Capacitance | 0.39 uF |
| Capacitance Tolerance | 10% |
| Voltage AC | 600 VAC |
| Voltage DC | 1000 VDC |
| Temperature Range | -55/+110°C |
| Rated Temperature | 85°C |
| Insulation Resistance | 76.923 GOhms |
| Max dV/dt | 2100 V/us |
| Resistance | 8.162 mOhms (100kHz) |
| Ripple Current | 9.481 Amps (100kHz 85C), 819 Amps (Peak) |
| Inductance | 16 nH |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)