


A759, Polymer Aluminum, 10 uF, 20%, 50 VDC, -55/+125°C, Lead Spacing = 2mm



Dimensions	
D	5mm +/-0.5mm
L	11mm +/-1mm
S	2mm +/-0.5mm
F	0.5mm +/-0.05mm
K	2.5mm MAX

Packaging Specifications	
Packaging:	Ammo
Packaging Quantity:	2000

General Information	
Series:	A759
Dielectric:	Polymer Aluminum
Description:	Single Ended, Polymer Aluminum
RoHS:	Yes
Lead:	Formed To 5mm
AEC-Q200:	No
Halogen Free:	Yes

Specifications	
Capacitance:	10 uF
Capacitance Tolerance:	20%
Voltage DC:	50 VDC, 57.5 VDC (Surge)
Temperature Range:	-55/+125°C
Rated Temperature:	125°C
Life:	2000 Hrs (+/-20% Initial Capacitance, 1.5x DF MAX, Leakage Within Limit)
Dissipation Factor:	12% 120Hz 20C
Resistance:	105 mOhms (100kHz 20C)
Ripple Current:	380 mAmps (100kHz 105C), 220 mAmps (100kHz 125C)
Leakage Current:	120 uA (2min 20°C)

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)