


T493C155K050BC6410

T493 HRA, Tantalum, MnO2 Tantalum, HRA, 1.5 uF, 10%, 50 VDC, SMD, MnO2, Molded, High Reliability, B (0.1%/1000 Hrs), 4.5 Ohms, 6032, Height Max = 2 8 mm



Click	horo	for	the	3D	mode	ı
CIICK	nere	101	1110	. אור.	HICKLE	1.

Dimensions	
Footprint	6032
L	6mm +/-0.3mm
W	3.2mm +/-0.3mm
Н	2.5mm +/-0.3mm
Т	0.13mm REF
S	1.3mm +/-0.3mm
F	2.2mm +/-0.1mm
Α	3.1mm MIN
В	0.5mm +/-0.15mm
E	2.4mm REF
G	2.8mm REF
P	0.5mm MIN
R	1mm REF
Χ	0.1mm +/-0.1mm

Packaging Specifications		
Packaging	T&R, 178mm	
Packaging Quantity	500	

General Information			
Series	T493 HRA		
Dielectric	MnO2 Tantalum		
Style	SMD Chip		
Description	SMD, MnO2, Molded, High Reliability		
Features	High Reliability		
RoHS	No		
Prop 65	★ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.		
SCIP Number	652b281f-d242-4453-bc44-0655d646cec3		
Termination	Hot Solder Dipped		
AEC-Q200	No		
Component Weight	224.2 mg		
Notes	P and R dimensions represents the minimum solderable area of the termination surface entirely below cutout (if one is present).		

Specifications	
Capacitance	1.5 uF
Capacitance Tolerance	10%
Voltage DC	50 VDC (85C), 33.5 VDC (125C)
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	6% 120Hz 25C
Failure Rate	B (0.1%/1000 Hrs)
Resistance	4.5 Ohms (100kHz 25C)
Leakage Current	0.8 uA (5min 25°C)
Testing and Reliability	10 Cycles Surge Current Testing At -55C And +85C Before Weibull

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)