



Click [here](#) for the 3D model.

### Dimensions

|    |                  |
|----|------------------|
| L  | 32mm +0.3/-0.7mm |
| H  | 33mm +0.1/-0.7mm |
| T  | 18mm +0.2/-0.7mm |
| S  | 27.5mm +/-0.4mm  |
| LL | 4mm +2mm         |
| F  | 0.8mm +/-0.05mm  |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | Tray |
| Packaging Quantity | 256  |

### General Information

|                  |                                 |
|------------------|---------------------------------|
| Series           | R76                             |
| Dielectric       | Double Metallized Polypropylene |
| Style            | Radial                          |
| Features         | Pulse                           |
| RoHS             | Yes                             |
| Lead             | Cut                             |
| AEC-Q200         | No                              |
| Component Weight | 22.81 g                         |

### Specifications

|                       |                                       |
|-----------------------|---------------------------------------|
| Capacitance           | 0.33 uF                               |
| Capacitance Tolerance | 5%                                    |
| Voltage AC            | 650 VAC                               |
| Voltage DC            | 1600 VDC                              |
| Temperature Range     | -55/+110°C                            |
| Rated Temperature     | 85°C                                  |
| Dissipation Factor    | 0.03% 1kHz, 0.06% 10kHz               |
| Insulation Resistance | 100 GOhms                             |
| Max dV/dt             | 2000 V/us                             |
| Resistance            | 7.23 mOhms (100kHz)                   |
| Ripple Current        | 11 Amps (100kHz 85C), 660 Amps (Peak) |
| Inductance            | 18 nH                                 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)