KEMET Part Number: CAN22X124KAGACTU


(CAN22X124KAGAC7800)

W

T B



CAN SMD Indust 250, Ceramic, 0.12 uF, 10%, C0G, SMD Chip, MLCC, AC Rated, 2225



		Termination:	Flexible Termination
		Marking:	No
		AEC-Q200:	No
		MSL:	1
Dimensions		Specifications	
Chip Size	2225	Capacitance:	0.12 uF

5.9mm +/-0.75mm

6.4mm +/-0.4mm 2.5mm +/-0.20mm

0.7mm +/-0.35mm

Packaging Specifications			
Packaging:	T&R, 180mm, Paper Tape		
Packaging Quantity:	500		

Specifications			
Capacitance:	0.12 uF		
Measurement Condition:	1 kHz 1.0Vrms		
Capacitance Tolerance:	10%		
Voltage AC:	250 VAC		
Dielectric Withstanding Voltage:	945 VDC		
Temperature Range:	-55/+125°C		
Temperature Coefficient:	COG		
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	15%, 1kHz 1.0Vrms		
Dissipation Factor:	0.1% 1 kHz 1.0Vrms		
Aging Rate:	0% Loss/Decade Hour		
Insulation Resistance:	8.333 GOhms		

General Information

CAN SMD Indust 250

SMD Chip, MLCC, AC Rated

Temperature Stable, Class I

SMD Chip

Series:

Style:

RoHS:

Description: Features:

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



55ce3

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)