



Click [here](#) for the 3D model.

Dimensions	
L	32mm +/-0.3mm
H	22mm +/-0.1mm
T	13mm +/-0.2mm
S	27.5mm +/-0.4mm
LL	30mm +5/-0mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	288

General Information	
Series	F43(X2)
Dielectric	Metallized Polypropylene
Style	Radial
RoHS	Yes
Qualifications	ENEC, UL
AEC-Q200	No

Specifications	
Capacitance	0.5 uF
Capacitance Tolerance	10%
Voltage AC	275 VAC
Temperature Range	-40/+100°C
Rated Temperature	100°C
Dissipation Factor	0.1% 1kHz (23C)
Insulation Resistance	1.5 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)