


C4AQ-P, Film, Metallized Polypropylene, Automotive DC Link, 10 uF, 5%, 600 VDC, Lead Spacing = 37.5mm



General Information	
Series:	C4AQ-P
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	DC Filtering
RoHS:	Yes
Lead:	4 Wire Leads
Qualifications:	AEC-Q200, IEC61071, EN61071, VDE0560
AEC-Q200:	Yes
Miscellaneous:	Rth = 29 C/W.

Dimensions	
L	41.5mm +0.6/-0.7mm
H	19mm +0.2/-0.7mm
T	24mm +0.4/-0.7mm
S	37.5mm +/-0.4mm
S1	10.2mm +/-0.4mm
LL	6mm -2mm
F	1.2mm +/-0.05mm

Specifications	
Capacitance:	10 uF
Capacitance Tolerance:	5%
Voltage DC:	600 VDC
Temperature Range:	-55/+125°C
Insulation Resistance:	3 GOhms
Max dV/dt:	30 V/us
Resistance:	11.44 mOhms (10kHz 70C)
Ripple Current:	9.3 Amps Irms (10kHz 75C), 300 Amps Ipk
Inductance:	8.1 nH

Packaging Specifications	
Packaging:	Bulk, Box
Packaging Quantity:	88

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)