



Note: '()' correspond to the letters used in the product bulletin

Click [here](#) for the 3D model.

Dimensions

| | |
|----|-----------------|
| D | 16.2mm +/-0.5mm |
| L | 34.7mm +/-1mm |
| L1 | 41mm MIN |
| LL | 40mm +/-2mm |
| F | 1mm +/-0.03mm |

Packaging Specifications

| | |
|-----------|------|
| Packaging | Tray |
|-----------|------|

General Information

| | |
|------------------|-------------------------|
| Series | PHA225 |
| Dielectric | Hybrid Polymer |
| Style | Axial |
| Description | Hybrid Axial Capacitors |
| RoHS | Yes |
| Lead | Wire Leads |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Halogen Free | Yes |
| Component Weight | 11 g |

Specifications

| | |
|-----------------------|--|
| Capacitance | 370 uF |
| Capacitance Tolerance | -10/+30% |
| Voltage DC | 63 VDC |
| Temperature Range | -40/+125°C |
| Rated Temperature | 125°C |
| Resistance | 145 mOhms (100Hz 20C), 6.1 mOhms (100kHz 125C) |
| Ripple Current | 39.5 Amps (100kHz 70C), 33.1 Amps (100kHz 90C), 26.5 Amps (100kHz 105C), 16.2 Amps (100kHz 125C) |
| Leakage Current | 116.5 uA (5min 20°C) |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)