



Click [here](#) for the 3D model.

### Dimensions

|    |                 |
|----|-----------------|
| L  | 26mm MAX        |
| H  | 19mm MAX        |
| T  | 10.5mm MAX      |
| S  | 22.5mm +/-0.4mm |
| LL | 6mm NOM         |
| F  | 0.8mm NOM       |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | Tray |
| Packaging Quantity | 264  |

### General Information

|                  |  |
|------------------|--|
| Series           | PHE850/F850  |
| Dielectric       | Metallized Polypropylene   |
| Style            | Radial   |
| Features         | EMI Safety   |
| RoHS             | Yes  |
| Lead             | Wire Leads   |
| Safety Class     | Y2   |
| Qualifications   | ENEC, UL, cUL  |
| AEC-Q200         | No   |
| THB Performance  | No   |
| Component Weight | 6.678 g  |
| Notes            | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

### Specifications

|                       |                                     |
|-----------------------|-------------------------------------|
| Capacitance           | 0.1 uF                              |
| Capacitance Tolerance | 10%                                 |
| Voltage AC            | 300 VAC (Y2)                        |
| Voltage DC            | 1250 VDC                            |
| Temperature Range     | -55/+110°C                          |
| Rated Temperature     | 110°C                               |
| Dissipation Factor    | 0.15% 1kHz, 0.2% 10kHz, 0.6% 100kHz |
| Insulation Resistance | 30 GOhms                            |
| Max dV/dt             | 100 V/us                            |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)