

R75MR3560AA30M

Aliases (75MR3560AA30M)

R75, Film, Metallized Polypropylene, General Purpose, 0.56 uF, 20%, 400 VDC, 85°C, Lead Spacing = 27.5mm



Click here for the 3D model.

Dimensions	,
L	32mm +0.3/-0.7mm
Н	17mm +0.1/-0.7mm
Т	9mm +0.2/-0.7mm
S	27.5mm +/-0.4mm
LL	4mm +2mm
F	0.8mm +/-0.05mm

Packaging Specifications		
Packaging	Tray	
Packaging Quantity	816	

General Information		
Series	R75	
Dielectric	Metallized Polypropylene	
Style	Radial	
Features	Pulse	
RoHS	Yes	
Lead	Cut	
AEC-Q200	No	
Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C.	

Specifications		
Capacitance	0.56 uF	
Capacitance Tolerance	20%	
Voltage AC	220 VAC	
Voltage DC	400 VDC	
Temperature Range	-55/+105°C	
Rated Temperature	85°C	
Dissipation Factor	0.05% 1kHz, 0.08% 10kHz	
Insulation Resistance	53.5714 GOhms	
Max dV/dt	130 V/us	
Resistance	11.4 mOhms (100kHz)	
Ripple Current	7.1 Amps (100kHz 85C), 73 Amps (Peak)	
Inductance	18 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)