



Click [here](#) for the 3D model.

Dimensions

| | |
|----|------------------|
| L | 11mm +/-0.2mm |
| L2 | 2.96mm MAX |
| W | 16.5mm +/-0.2mm |
| H | 6.05mm +/-0.2mm |
| H1 | 9.25mm +1mm |
| S | 15mm +/-0.2mm |
| S1 | 2.54mm +/-0.2mm |
| S2 | 5.08mm +/-0.2mm |
| LL | 3.2mm +1mm |
| F | 0.5mm +/-0.05mm |
| E | 0.2mm MAX |
| G | 0.3mm MAX |
| X | 0.35mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|------|
| Packaging | Tube |
| Packaging Quantity | 43 |

General Information

| | |
|------------|----------------------|
| Series | MDK/F68 |
| Dielectric | Metallized Polyester |
| Style | Dual-In-Line |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |

Specifications

| | |
|-----------------------|----------------------------------|
| Capacitance | 2.2 uF |
| Capacitance Tolerance | 5% |
| Voltage AC | 63 VAC |
| Voltage DC | 100 VDC |
| Temperature Range | -55/+125°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.8% 1kHz, 1.5% 10kHz, 5% 100kHz |
| Insulation Resistance | 2.2727 GOhms |
| Inductance | 4 nH |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)