



Click [here](#) for the 3D model.

Dimensions

| | |
|----|------------------|
| D | 3.18mm +/-0.13mm |
| L | 6.35mm +/-0.79mm |
| L2 | 10.72mm MAX |
| LL | 38.1mm +/-6.35mm |
| F | 0.51mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|------|
| Packaging | Tray |
| Packaging Quantity | 40 |

General Information

| | |
|----------------|--|
| Series | T256 CSS33 |
| Dielectric | MnO2 Tantalum |
| Style | Axial Hermetic |
| Description | Axial, Solid Tantalum, Hermetically Sealed, Military, CSS33 Style |
| Features | Extended Capacitance, Low Leakage, Low ESR, Low DF |
| RoHS | No |
| Prop 65 | ⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov . |
| SCIP Number | bee1eed4-5fec-4214-9f43-620c5b22071f |
| Termination | Lead (SnPb) |
| Lead | Wire Leads |
| Qualifications | CSS33 |
| AEC-Q200 | No |
| Construction | Hermetic |
| Notes | Uninsulated. Caution: Black Band Indicates Negative End Of Case. |

Specifications

| | |
|-----------------------|--|
| Capacitance | 4.7 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 15 VDC (85C), 12 VDC (125C Surge), 0.15 VDC (125C Reverse) |
| Temperature Range | -55/+125°C |
| Dissipation Factor | 4% |
| Failure Rate | C (0.01%/1000 Hrs) |
| Resistance | 0.9 Ohms (100kHz) |
| Ripple Current | 316 mAmps (100kHz) |
| Leakage Current | 0.5 uA |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)