
## KEMET Part Number: MMK7.5394K100K03L16.5TR18

(F601KK394K100L, MMK7,5394K100K03L16,5TR18)



MMK/F601, Film, Metallized Polyester, General Purpose, 0.39 uF, 10%, 100 VDC, 85°C, Lead Spacing = 7.5mm



General Information	
Series:	MMK/F601
Dielectric:	Metallized Polyester
Style:	Radial
Features:	DC Multipurpose Applicatiions
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No
Notes:	Not For New Design, Please Check Possible Alternative Parts (AltPart).

Dimensions		
L	10mm MAX	
Н	11mm MAX	
Т	5mm MAX	
S	7.5mm +0.6/-0.1mm	
H0	16mm NOM	
F	0.6mm NOM	

Packaging Specifications	
Packaging:	T&R
Packaging Quantity:	1300

Specifications		
Capacitance:	0.39 uF	
Capacitance Tolerance:	10%	
Voltage AC:	63 VAC	
Voltage DC:	100 VDC, 77.5 VDC (100C)	
Temperature Range:	-55/+100°C	
Rated Temperature:	85°C	
Dissipation Factor:	0.8% 1kHz, 1.5% 10kHz	
Insulation Resistance:	12.8205 GOhms	
Max dV/dt:	20 V/us	
Inductance:	6 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)