

**KEMET Part Number: MMK37.5185M400R05L4TRAY**  
(F601RF185M400C, MMK37,5185M400R05L4TRAY)

**KEMET**

a YAGEO company

MMK/F601, Film, Metallized Polyester, General Purpose, 1.8 uF, 20%, 400 VDC, 85°C, Lead Spacing = 37.5mm



**General Information**

<b>Series:</b>	MMK/F601
<b>Dielectric:</b>	Metallized Polyester
<b>Style:</b>	Radial
<b>Features:</b>	DC Multipurpose Applications
<b>RoHS:</b>	Yes
<b>Lead:</b>	Wire Leads
<b>AEC-Q200:</b>	No
<b>Notes:</b>	Not For New Design, Please Check Possible Alternative Parts (AltPart).

**Dimensions**

<b>L</b>	41mm MAX
<b>H</b>	24mm MAX
<b>T</b>	13mm MAX
<b>S</b>	37.5mm +/-0.5mm
<b>LL</b>	5mm NOM
<b>F</b>	1mm NOM

**Specifications**

<b>Capacitance:</b>	1.8 uF
<b>Capacitance Tolerance:</b>	20%
<b>Voltage AC:</b>	200 VAC
<b>Voltage DC:</b>	400 VDC, 310 VDC (100C)
<b>Temperature Range:</b>	-55/+100°C
<b>Rated Temperature:</b>	85°C
<b>Dissipation Factor:</b>	1% 1kHz
<b>Insulation Resistance:</b>	5.5556 GOhms
<b>Max dV/dt:</b>	5 V/us
<b>Inductance:</b>	6 nH

**Packaging Specifications**

<b>Packaging:</b>	Tray
<b>Packaging Quantity:</b>	140

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

**KEMET**

a YAGEO company

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)