



Click [here](#) for the 3D model.

Dimensions

| | |
|-----------|--|
| Chip Size | 0805 |
| L | 2.032mm +/-0.381mm (0.08 in +/-0.015 in) |
| W | 1.27mm +/-0.381mm (0.05 in +/-0.015 in) |
| T | 1.397mm MAX (0.055 in MAX) |

Packaging Specifications

| | |
|--------------------|--------------------------|
| Packaging | T&R, 180mm, Plastic Tape |
| Packaging Quantity | 2500 |

General Information

| | |
|--------------|--|
| Series | SMD Mil PRF123 |
| Style | SMD Chip |
| Description | SMD Chip, Ultra Stable |
| RoHS | No |
| Prop 65 | ⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov . |
| SCIP Number | 646e40c8-ce81-456e-b9ed-50112f3d27a5 |
| Termination | Nickel |
| Failure Rate | N/A |
| AEC-Q200 | No |
| Shelf Life | 78 Weeks |
| MSL | 1 |

Specifications

| | |
|--|---------------------|
| Capacitance | 56 pF |
| Capacitance Tolerance | 5% |
| Voltage DC | 50 VDC |
| Dielectric Withstanding Voltage | 125 VDC |
| Temperature Range | -55/+125°C |
| Temperature Coefficient | BP |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC) | 15%, 1MHz 1.0Vms |
| Dissipation Factor | 2.5% |
| Insulation Resistance | 100 GOhms |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)