


T493D226K016CH6310

T493 HRA, Tantalum, MnO2 Tantalum, HRA, 22 uF, 10%, 16 VDC, SMD, MnO2, Molded, High Reliability, C (0.01%/1000 Hrs), 800 mOhms, 7343, Height Max = 3.1mm

CATHODE (-) END VIEW






ANODE (+) END VIEW

R

Ρ

- S -G -S-BOTTOM VIEW A È



В

Termination cutout	
at KEMET's option,	
either end	

Click here for the 3D model.

Dimensions	
Footprint	7343
L	7.3mm +/-0.3mm
W	4.3mm +/-0.3mm
Н	2.8mm +/-0.3mm
Т	0.13mm REF
S	1.3mm +/-0.3mm
F	2.4mm +/-0.1mm
А	3.8mm MIN
В	0.5mm +/-0.15mm
E	3.5mm REF
G	3.5mm REF
Р	0.5mm MIN
R	1mm REF
Х	0.1mm +/-0.1mm

т

Packaging Specifications	
Packaging	T&R, 178mm
Packaging Quantity	500

General Information		
Series	T493 HRA	
Dielectric	MnO2 Tantalum	
Style	SMD Chip	
Description	SMD, MnO2, Molded, High Reliability	
Features	High Reliability	
RoHS	No	
Prop 65	A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
Termination	Solder Coated	
AEC-Q200	No	
Component Weight	412.33 mg	
Notes	P and R dimensions represents the minimum solderable area of the termination surface entirely below cutout (if one is present).	

22 uF
10%
16 VDC (85C), 10.72 VDC (125C)
-55/+125°C
85°C
6% 120Hz 25C
C (0.01%/1000 Hrs)
0.8 Ohms (100kHz 25C)
3.5 uA (5min 25°C)
10 Cycles Surge Current Testing At -55C And +85C After Weibull

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)