
## KEMET Part Number: CWR11MH685MAA

(T492D685M035AH4250)



T492 CWR11, Tantalum, MnO2 Tantalum, Military/High Reliability, 6.8 uF, 20%, 35 VDC, SMD, MnO2, Molded, Military Equivalent, A (Non-ER), 1.3 Ohms, 7343, Height Max = 3.1mm



| Dimensions |                 |  |
|------------|-----------------|--|
| Footprint  | 7343            |  |
| L          | 7.3mm +/-0.3mm  |  |
| W          | 4.3mm +/-0.3mm  |  |
| Н          | 2.8mm +/-0.3mm  |  |
| Т          | 0.13mm REF      |  |
| S          | 1.3mm +/-0.3mm  |  |
| F          | 2.4mm +/-0.1mm  |  |
| В          | 0.5mm +/-0.15mm |  |
| E          | 3.5mm REF       |  |
| G          | 3.5mm REF       |  |
| К          | 1mm MIN         |  |
| Р          | 0.5mm MIN       |  |
| R          | 1mm REF         |  |
| Х          | 0.1mm +/-0.1mm  |  |

| Packaging Specifications |            |  |
|--------------------------|------------|--|
| Packaging:               | T&R, 178mm |  |
| Packaging Quantity:      | 500        |  |

| O su su l lu        | 6  |
|---------------------|--|
| General Information |  |
| Series:             | T492 CWR11   |
| Dielectric:         | MnO2 Tantalum  |
| Style:              | SMD Chip   |
| Description:        | SMD, MnO2, Molded, Military<br>Equivalent  |
| RoHS:               | No   |
| Prop 65:            | WARNING: Cancer<br>and reproductive harm -<br>www.p65warnings.ca.gov.  |
| Termination:        | Solder Coated  |
| Qualifications:     | MIL-PRF-55365/8, CWR11 Style   |
| AEC-Q200:           | No   |
| Component Weight:   | 412.33 mg  |
| Notes:              | Note: When Option C Is Selected<br>For Lead Material, Add An<br>Additional 0.38mm To The<br>Tolerances For "L", "W", "H",<br>"K" ,"F" And "S". |
| MSL:                | 1  |

| Specifications           |                                       |  |
|--------------------------|---------------------------------------|--|
| Capacitance:             | 6.8 uF                                |  |
| Capacitance Tolerance:   | 20%                                   |  |
| Voltage DC:              | 35 VDC (85C), 23.45 VDC<br>(125C)     |  |
| Temperature Range:       | -55/+125°C                            |  |
| Rated Temperature:       | 85°C                                  |  |
| Dissipation Factor:      | 6% 120Hz 25C                          |  |
| Failure Rate:            | A (Non-ER)                            |  |
| Resistance:              | 1.3 Ohms (100kHz 25C)                 |  |
| Leakage Current:         | 2.4 uA (5min 25°C)                    |  |
| Testing and Reliability: | Surge Testing At 25C After<br>Weibull |  |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)