

EFS(01)-240X80T0800

Aliases (UFSEFS010JT080)

 ${\sf KEMET, EFS, Flex\, Suppressors, Noise\, Suppression}$

		Т
	W	
L		

Click here for the 3D model.

Dimensions	
Sheet Size	240x80mm
L	240mm NOM
W	80mm NOM
Т	0.1mm NOM

Packaging Specifications	
Component Weight	11.3 g

General Information				
Series	EFS			
Style	Sheet			
Description	Flex Suppressor Super High Frequency Type			
Features	Super High Frequency			
RoHS	Yes			
Qualifications	UL94 V-0, UL File No. E176124			
Environment	RoHS Compliant, Halogen Free, PVC Free, Lead Free, Red Phosphorus Free			

Specifications		
Temperature Range	-40/+105°C	
Permeability	10 u At 3MHz	
Effective Frequency	3 GHz to 40GHz	
Specific Gravity	4.5 TYP	
Surface Resistivity	100 MOhm/sq. TYP	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)