


T543D477M2R5AHW005

T543 HRA, Tantalum, Polymer Tantalum, HRA, 470 uF, 20%, 2.5 VDC, SMD, Polymer, Molded, High Reliability, Up Screening, N/A, 5 mOhms, 7343, Height Max = 3.1mm



	Click	here	for	the	3D	mode
--	-------	------	-----	-----	----	------

Dimensions	,
Footprint	7343
L	7.3mm +/-0.3mm
W	4.3mm +/-0.3mm
Н	2.8mm +/-0.3mm
Т	0.13mm REF
S	1.3mm +/-0.3mm
F	2.4mm +/-0.1mm
A	3.8mm MIN
В	0.5mm +/-0.15mm
E	3.5mm REF
G	3.5mm REF
Р	0.9mm REF
R	1mm REF
Χ	0.1mm +/-0.1mm

Packaging Specifications				
Packaging	T&R, 178mm			
Packaging Quantity	500			

General Information	n	
Series	T543 HRA	
Dielectric	Polymer Tantalum	
Style	SMD Chip	
Description	SMD, Polymer, Molded, High Reliability, Up Screening	
Features	Non-Combustible, Up Screening, Low ESR, High Reliability	
RoHS	No	
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	b064b03e-bd75-42af-b342-1fe94dec2340	
Termination	Solder Coated	
AEC-Q200	No	
Component Weight	352.36 mg	
Shelf Life	52 Weeks	
MSL	3	

470 uF
20%
2.5 VDC (105C)
-55/+105°C
105°C
60C, 90% RH, 500 Hours
10% 120Hz 25C
N/A
5 mOhms (100kHz)
6708 mA (rms, 100kHz 45C)
117.5 uA (5min 25°C)
10 Cycles Surge Current Testing At -55C And +85C

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)