


USEQGSEACH4180

Aliases (USEQGSEACH4180)

KEMET, QGS, Gas Detection, SMD, Infrared, Small SMD Package, 12C Communication Compatible, High Dynamic Range



Click here for the 3D model.

Dimensions		
L	5.65mm NOM	
W	3.7mm NOM	
Т	1.55mm MAX	

Packaging Specifications		
Packaging	T&R, 178mm	
Packaging Quantity	800	
Component Weight	70 mg	

General Information		
Series	QGS	
Туре	Gas Detection	
Style	SMD	
Description	12C	
Features	Small SMD Package, 12C Communication Compatible, High Dynamic Range	
RoHS	With Exemptions	
REACH	SVHC (PZT - CAS 12626-81-2)	
SCIP Number	bc4e3452-d0d0-4c97-93bd-778b4e41f2f2	
Qualifications	REACH	
MSL	3	

Specifications	
Temperature Range	-40/+85°C
Power Supply Voltage	1.75 - 3.6 V
Current	1 - 23 uA (Supply Current, Typical)
D*	$2.5 \times 10^8 $ cm sqrt(Hz)/ W
NEP	$2.7 \times 10^{-10} \text{ W/sqrt(Hz)}$
Time Constant	10ms (10-20 Hz peak)
Field of View	90 degrees
Element Size	0.64mm x 0.64mm
Filter	3.3um, BW: 160nm, Gas: CH4

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)