


R752R41505000K

Aliases (752R41505000K)

R752, Film, Metallized Polypropylene, General Purpose, 1.5 uF, 10%, 400 VDC, 85°C, Lead Spacing = 27.5mm



Click here for the 3D model.

Dimensions	,
L	32mm +/-0.3mm
Н	22mm +0.1mm
T	13mm +/-0.2mm
S	27.5mm +/-0.4mm
LL	25mm +2/-1mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	288

General Information		
Series	R752	
Dielectric	Metallized Polypropylene	
Style	Radial	
Features	Pulse, Capacitive Power Supply	
RoHS	Yes	
Lead	Wire Leads	
AEC-Q200	No	
Component Weight	9.3 g	

Specifications	
Capacitance	1.5 uF
Capacitance Tolerance	10%
Voltage AC	230 VAC
Voltage DC	400 VDC, 240 VDC (105C)
Temperature Range	-55/+105°C
Rated Temperature	85°C
Dissipation Factor	0.06% 1kHz
Insulation Resistance	20 GOhms
Max dV/dt	130 V/us
Inductance	18 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)