


## T493C106K035CH6310

T493 HRA, Tantalum, MnO2 Tantalum, HRA, 10 uF, 10%, 35 VDC, SMD, MnO2, Molded, High Reliability, C (0.01%/1000 Hrs), 2 Ohms, 6032, Height Max = 2 8mm



Click here for the 3D model.

| Dimensions |                 |
|------------|-----------------|
| Footprint  | 6032            |
| L          | 6mm +/-0.3mm    |
| W          | 3.2mm +/-0.3mm  |
| Н          | 2.5mm +/-0.3mm  |
| Т          | 0.13mm REF      |
| S          | 1.3mm +/-0.3mm  |
| F          | 2.2mm +/-0.1mm  |
| Α          | 3.1mm MIN       |
| В          | 0.5mm +/-0.15mm |
| E          | 2.4mm REF       |
| G          | 2.8mm REF       |
| Р          | O.5mm MIN       |
| R          | 1mm REF         |
| X          | 0.1mm +/-0.1mm  |

| Packaging Specifications |            |
|--------------------------|------------|
| Packaging                | T&R, 178mm |
| Packaging Quantity       | 500        |

| General Information |   |
|---------------------|---|
| Series              | T493 HRA  |
| Dielectric          | MnO2 Tantalum   |
| Style               | SMD Chip  |
| Description         | SMD, MnO2, Molded, High Reliability   |
| Features            | High Reliability  |
| RoHS                | No  |
| Prop 65             | ▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.  |
| SCIP Number         | 1dd2e1b8-26dd-4d52-927c-6f9d519011aa  |
| Termination         | Solder Coated   |
| AEC-Q200            | No  |
| Component<br>Weight | 224.2 mg  |
| Notes               | P and R dimensions represents the minimum solderable area of the termination surface entirely below cutout (if one is present). |

| Specifications             |   |
|----------------------------|---|
| Capacitance                | 10 uF   |
| Capacitance<br>Tolerance   | 10%   |
| Voltage DC                 | 35 VDC (85C), 23.45 VDC (125C)                                    |
| Temperature<br>Range       | -55/+125°C  |
| Rated<br>Temperature       | 85°C  |
| Dissipation Factor         | 6% 120Hz 25C  |
| Failure Rate               | C (0.01%/1000 Hrs)  |
| Resistance                 | 2 Ohms (100kHz 25C)   |
| Leakage Current            | 3.5 uA (5min 25°C)  |
| Testing and<br>Reliability | 10 Cycles Surge Current Testing At -55C And<br>+85C After Weibull |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)