
KEMET Part Number: 100HS36N122JC

(100HS36N122JC)



HS RAD-LDD Space C0G HV, Ceramic, 1200 pF, 5%, 10000 VDC, C0G, Lead Spacing = 34.92mm



Dimensions	
L	36.83mm
Н	18.29mm MAX
Т	6.89mm MAX
S	34.925mm +/-0.762mm
LL	31.75mm MIN
F	0.635mm NOM

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	1	

General Information		
Series:	HS RAD-LDD Space C0G HV	
Style:	Radial	
RoHS:	No	
Prop 65: SCIP Number:	WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov. 2340ecb8-2b2f-4a8e-990d- e9ce728f4668	
Termination:	Lead (SnPb)	
Failure Rate:	N/A	
Testing and Reliability:	CSAM Burn-in	
AEC-Q200:	No	

Specifications		
Capacitance:	1200 pF	
Capacitance Tolerance:	5%	
Voltage DC:	10000 VDC	
Dielectric Withstanding Voltage:	15000 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	COG	
Dissipation Factor:	0.15%	
Insulation Resistance:	100 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)