

T493X475M050BH6110

T493 HRA, Tantalum, MnO2 Tantalum, HRA, 4.7 uF, 20%, 50 VDC, SMD, MnO2, Molded, High Reliability, B (0.1%/1000 Hrs), 900 mOhms, 7343, Height Max = 4.3mm

CATHODE (-) END VIEW SIDE VIEW W - B Ĥ т /ł X -S- -- G -- - S-BOTTOM VIEW ANODE (+) END VIEW Termination cutout at KEMET's option, either end - A -Glue pad Ė shape/design at KEMET's option 1 Ρ R

В

Ê

1

General Informatio	n
Series	T493 HRA
Dielectric	MnO2 Tantalum
Style	SMD Chip
Description	SMD, MnO2, Molded, High Reliability
Features	High Reliability
RoHS	No
Prop 65	A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
SCIP Number	1dd2e1b8-26dd-4d52-927c-6f9d519011aa
Termination	Solder Coated
AEC-Q200	No
Component Weight	654.04 mg

Click here for the 3D model.

7343
7.3mm +/-0.3mm
4.3mm +/-0.3mm
4mm +/-0.3mm
0.13mm REF
1.3mm +/-0.3mm
2.4mm +/-0.1mm
3.8mm MIN
0.5mm +/-0.15mm
3.5mm REF
3.5mm REF
1.7mm REF
1mm REF
0.1mm +/-0.1mm

Packaging Specifications		
Packaging	T&R, 178mm	
Packaging Quantity	500	

Specifications		
Capacitance	4.7 uF	
Capacitance Tolerance	20%	
Voltage DC	50 VDC (85C), 33.5 VDC (125C)	
Temperature Range	-55/+125°C	
Rated Temperature	85°C	
Dissipation Factor	4% 120Hz 25C	
Failure Rate	B (0.1%/1000 Hrs)	
Resistance	0.9 Ohms (100kHz 25C)	
Leakage Current	2.4 uA (5min 25°C)	
Testing and Reliability	Standard Testing Only	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)