


TRS3-20MCR00

Aliases (USED20MCR00000)

KEMET, TRS, Thermal Reed Switch, Axial, 2.5C Temperature Accuracy, High Reliability, High-Speed Response, Long Operational Life, Excellent Environmental Durability, High Temperature Accuracy, 20°C, Make



General Information Series TRS Thermal Reed Switch Type Style Description Thermal Reed Switch High Reliability, High-Speed Response, Long Features Operational Life, Excellent Environmental Durability, High Temperature Accuracy Lead Wire Leads RoHS Yes

| Click here for the 3D model | Click | here | for | the | 3D | model. |
|-----------------------------|-------|------|-----|-----|----|--------|
|-----------------------------|-------|------|-----|-----|----|--------|

| Dimensions | | |
|------------|-----------|--|
| D | 7.7mm NOM | |
| L | 54mm NOM | |
| LL | 200mm NOM | |

| Packaging Specifications | |
|--------------------------|----------------|
| Packaging | Rubberband Box |
| Packaging Quantity | 600 |
| Component Weight | 8.1 a |

| 20C +/-2.5C |
|--|
| -20/+130°C |
| Make |
| 200 VDC MAX (Opening/Closing), 1500 VAC/1 minute or 1800 VAC/1 second |
| 140 VAC MAX (Opening/Closing) |
| 0.5 Amps AC/DC MAX (Opening/Closing), 1 mAmps MIN (5VDC, Opening/Closing) |
| 150 mOhms MAX (Contact Resistance) |
| 35 W (AC) |
| 140 V (AC); 200 V (DC) |
| 10C Maximum |
| |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)