

R76T11560SE40J

Aliases (76T11560SE40J)

R76, Film, Double Metallized Polypropylene, Automotive Grade, 5600 pF, 5%, 1600 VDC, 85°C, Lead Spacing = 15mm



Click [here](#) for the 3D model.

Dimensions

| | |
|----|------------------|
| L | 18mm +0.3/-0.5mm |
| H | 10mm +0.1/-0.5mm |
| T | 4mm +0.2/-0.5mm |
| S | 15mm +/-0.4mm |
| LL | 4mm +2mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 2500 |

General Information

| | |
|----------------|---------------------------------|
| Series | R76 |
| Dielectric | Double Metallized Polypropylene |
| Style | Radial |
| Features | Automotive Grade, Pulse |
| RoHS | Yes |
| Lead | Cut |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |

Specifications

| | |
|-----------------------|---------------------------------------|
| Capacitance | 5600 pF |
| Capacitance Tolerance | 5% |
| Voltage AC | 650 VAC |
| Voltage DC | 1600 VDC |
| Temperature Range | -55/+110°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz |
| Insulation Resistance | 100 GOhms |
| Max dV/dt | 6000 V/us |
| Resistance | 113.68 mOhms (100kHz) |
| Ripple Current | 1.6 Amps (100kHz 85C), 34 Amps (Peak) |
| Inductance | 10 nH |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)