
KEMET Part Number: SMR10823J400A04L4BULK

(F211AP823J400C)



SMR/F211, Film, Metallized PPS, General Purpose, 0.082 uF, 5%, 400 VDC, 125°C, Lead Spacing = 10mm



General Information		
Series:	SMR/F211	
Dielectric:	Metallized PPS	
Style: Radial		
Features:	Audio Applications	
RoHS:	Yes	
Lead:	Wire Leads	
AEC-Q200:	No	
Miscellaneous:	The rated voltage decreases 2%/ C between +125C and +150C.	
Notes:	Case Size = AP.	

Specifications

Dimensions			
L	13mm -0.5mm		
Н	12mm -0.5mm		
Т	6mm -0.5mm		
S	10mm +/-0.4mm		
LL	4mm +1mm		
F	0.6mm +/-0.05mm		
G	0.5mm NOM		

13mm -0.5mm	Capacitance:	0.082 uF
12mm -0.5mm	Capacitance Tolerance:	5%
6mm -0.5mm	<u> </u>	200 VAC
10mm +/-0.4mm	Voltage AC:	
4mm +1mm	Voltage DC:	400 VDC
	Temperature Range:	-55/+150°C
0.6mm +/-0.05mm	Rated Temperature:	125°C
0.5mm NOM	Dissipation Factor:	0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz
	Insulation Resistance:	30 GOhms
pecifications	Max dV/dt:	25 V/us

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	600	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)