
KEMET, EF2, Relays, Signal



Click here for the 3D model.

Dimensions		
L	15mm MAX	
W	7.5mm MAX	
Н	10mm MAX	
LL	1mm +/-0.1mm	
S	5.08mm +/-0.2mm	
S1	2.54mm +/-0.2mm	
F	1mm +/-0.1mm	
F1	2mm +/-0.1mm	

Packaging Specifications		
Packaging	T&R	

General Information		
Series	EF2	
Style	SMD	
Description	Miniature Signal Relay, Non-latch, Minimum Footprint	
Features	Compact and light weight. FCC (1500 V) and Telcordia (2500 V) surge capacity. UL recognized and CSA certified. Low power consumption (30-70 mW). Basic insulation class for EN60950.	
RoHS	Yes	
Coil Type	Single Coil (Non-Latching)	

Specifications	
Temperature Range	-40/+85°C
Coil Voltage	4.5 V
Coil Resistance	405 Ohms +/-10%
Contact Form	2 Form C (DPDT)
Contact Material	Silver Alloy With Gold Alloy Overlay
Voltage Characteristics	3.38 (Operate) / 0.45 (Release)
Switching Power	30 W, 62.5 VA
Switching Voltage DC	220 V
Switching Voltage AC	250 VAC
Switching Current	1A
Contact Current Class	>10A
Carrying Current	2 Amps
Contact Resistance	75 mOhms
Operation Time	Approximately 3ms
Release Time	Approximately 2ms
Insulation Resistance	1GOhms
Withstanding Voltage	1000 VAC (1min) 1500 V Surge

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)