



Click [here](#) for the 3D model.

Dimensions

| | |
|---|----------------|
| L | 7.3mm +/-0.3mm |
| W | 4.3mm +/-0.3mm |
| H | 1.9mm +/-0.2mm |
| S | 1.3mm +/-0.3mm |
| F | 2.4mm +/-0.1mm |

Packaging Specifications

| | |
|--------------------|------------|
| Packaging | T&R, 180mm |
| Packaging Quantity | 1000 |

General Information

| | |
|------------------|---------------------------------|
| Series | A720 |
| Dielectric | Polymer Aluminum |
| Style | SMD Chip |
| Description | Surface Mount, Polymer Aluminum |
| RoHS | Yes |
| Termination | Nickel Palladium Gold |
| Qualifications | UL94V-0 |
| AEC-Q200 | No |
| Halogen Free | Yes |
| Component Weight | 141 mg |
| Notes | V/7343-21. |
| Footprint | 7343 |
| Shelf Life | 104 Weeks |
| MSL | 3 |

Specifications

| | |
|-----------------------|-----------------------|
| Capacitance | 560 uF |
| Capacitance Tolerance | 20% |
| Voltage DC | 2 VDC |
| Temperature Range | -55/+105°C |
| Rated Temperature | 105°C |
| Dissipation Factor | 6% 120Hz 25C |
| Resistance | 3 mOhms (100kHz 25C) |
| Ripple Current | 11690 mA (rms 100kHz) |
| Leakage Current | 67.2 uA (5min 25°C) |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)