

KEMET Part Number: R474W41500001M
(474W41500001M)

R47 X2 440 VAC, Film, Metallized Polypropylene, Safety, 1.5 uF, 20%, 440 VAC (X2), 1000 VDC, 110°C, Lead Spacing = 37.5mm



General Information

Series:	R47 X2 440 VAC
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	EMI Safety
RoHS:	Yes
Lead:	Cut
Safety Class:	X2
Qualifications:	ENEC, UL, cUL
AEC-Q200:	No

Dimensions

L	41.5mm +0.3/-0.7mm
H	32mm +0.1/-0.7mm
T	19mm +0.3/-0.7mm
S	37.5mm +/-0.4mm
LL	4mm +2mm
F	1mm +/-0.05mm

Specifications

Capacitance:	1.5 uF
Capacitance Tolerance:	20%
Voltage AC:	440 VAC (X2)
Voltage DC:	1000 VDC
Temperature Range:	-40/+110°C
Rated Temperature:	110°C
Dissipation Factor:	0.1% 1kHz
Insulation Resistance:	20 GOhms
Max dV/dt:	150 V/us

Packaging Specifications

Packaging:	Tray
Packaging Quantity:	192

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)