


## VCR40M101JWS

VCR Indust COG HVHT200C, Ceramic, 100 pF, 5%, 1000 VDC, COG, Commercial, High Temperature, HighVoltage, Lead Spacing = 6.35mm



Cliala	h	f ~ - + h	20	model

Dimensions	
L	8.89mm MAX
W	10.16mm MAX
Т	6.98mm MAX
S	6.35mm +/-0.76mm
LL	3.175mm MIN
F	0.635mm +/-0.051mm

Packaging Specifications				
Packaging	Bulk, Bag			
Packaging Quantity	1			

General Information		
Series	VCR Indust COG HVHT200C	
Style	Radial	
Description	Commercial, High Temperature, HighVoltage	
Features	Commercial	
RoHS	No	
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	8b930311-e6ed-4436-9857-2b5f449be092	
Termination	Lead (SnPb)	
Failure Rate	N/A	
Testing and Reliability	Standard	
AEC-Q200	No	

Specifications	
Capacitance	100 pF
Capacitance Tolerance	5%
Voltage DC	1000 VDC
Dielectric Withstanding Voltage	1500 VDC
Temperature Range	-55/+200°C
Temperature Coefficient	COG
Dissipation Factor	0.15% 1 MHz 1.0Vrms
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)