
## KEMET Part Number: R474I2470JE01M (474I2470JE01M)



R47 X2 440 VAC, Film, Metallized Polypropylene, Automotive Safety, 0.047 uF, 20%, 440 VAC (X2), 1000 VDC, 110°C, Lead Spacing = 15mm



Dimensions		
L	18mm +/-0.5mm	
Н	13.5mm +0.1/-0.5mm	
Т	7.5mm +0.2/-0.5mm	
S	15mm +/-0.4mm	
LL	4mm +0.5mm	
F	0.6mm +/-0.05mm	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	1000	

General Information		
Series:	R47 X2 440 VAC	
Dielectric:	Metallized Polypropylene	
Style:	Radial	
Features:	Automotive Grade, EMI Safety	
RoHS:	Yes	
Lead:	Cut	
Safety Class:	X2	
Qualifications:	AEC-Q200, ENEC, UL, cUL	
AEC-Q200:	Yes	

Specifications		
Capacitance:	0.047 uF	
Capacitance Tolerance:	20%	
Voltage AC:	440 VAC (X2)	
Voltage DC:	1000 VDC	
Temperature Range:	-40/+110°C	
Rated Temperature:	110°C	
Dissipation Factor:	0.1% 1kHz	
Insulation Resistance:	100 GOhms	
Max dV/dt:	600 V/us	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)