



Click [here](#) for the 3D model.

### Dimensions

Chip Size	0805
L	2.01mm +0.3/-0.25mm (0.079 in +0.012/-0.01 in)
W	1.27mm +0.3/-0.25mm (0.05 in +0.012/-0.01 in)
T	1.57mm MAX (0.062 in MAX)
B	0.51mm +/-0.25mm (0.02 in +/-0.01 in)

### Packaging Specifications

Packaging	T&R
Packaging Quantity	4000

### General Information

Series	SMD MIL COG PRF32535
Style	SMD Chip
Description	SMD, Low ESR, MIL-PRF-32535
RoHS	No
Prop 65	<b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a>
Termination	Solder Plated
Failure Rate	N/A
Qualifications	MIL-PRF-32535 M-Level
AEC-Q200	No
Shelf Life	78 Weeks
MSL	1

### Specifications

Capacitance	10 pF
Capacitance Tolerance	5%
Voltage DC	200 VDC
Dielectric Withstanding Voltage	500 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	COG
Dissipation Factor	0.15% 1 MHz 25C
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	100 GOhms

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)