



Click [here](#) for the 3D model.

Dimensions

Chip Size	1812
L	4.57mm +1.02/-0.38mm (0.18 in +0.04/-0.015 in)
W	3.18mm +0.76/-0.38mm (0.125 in +0.03/-0.015 in)
T	1.295mm +1.115/-0.735mm (0.051 in +0.044/-0.029 in)
B	0.51mm +0.63/-0.25mm (0.02 in +0.025/-0.01 in)

Packaging Specifications

Packaging	T&R, 178mm, Plastic Tape
Packaging Quantity	1100

General Information

Series	SMD Mil PRF55681
Style	SMD Chip
RoHS	No
Prop 65	⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov .
SCIP Number	de44f0ec-7e7c-4120-b42e-f63f667919b6
Termination	Lead (SnPb)
Failure Rate	P (0.1%/1000 Hrs)
Testing and Reliability	MIL-PRF-55681
Qualifications	MIL-PRF-55681
AEC-Q200	No
Miscellaneous	Termination Description: SolderCoat 60-40.
Shelf Life	78 Weeks
MSL	1

Specifications

Capacitance	1800 pF
Capacitance Tolerance	5%
Voltage DC	100 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	BP

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)