



Click [here](#) for the 3D model.

### Dimensions

|    |                  |
|----|------------------|
| L  | 32mm +0.3/-0.7mm |
| H  | 15mm +0.1/-0.7mm |
| T  | 24mm +0.2/-0.7mm |
| S  | 27.5mm +/-0.4mm  |
| LL | 4mm +2mm         |
| F  | 0.8mm +/-0.05mm  |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | Tray |
| Packaging Quantity | 336  |

### General Information

|                  |                                 |
|------------------|---------------------------------|
| Series           | R76                             |
| Dielectric       | Double Metallized Polypropylene |
| Style            | Radial                          |
| Features         | Pulse                           |
| RoHS             | Yes                             |
| Lead             | Cut                             |
| AEC-Q200         | No                              |
| Component Weight | 10.5 g                          |

### Specifications

|                       |  |
|-----------------------|--|
| Capacitance           | 0.22 uF                                |
| Capacitance Tolerance | 5%                                     |
| Voltage AC            | 600 VAC                                |
| Voltage DC            | 1000 VDC                               |
| Temperature Range     | -55/+110°C                             |
| Rated Temperature     | 85°C                                   |
| Dissipation Factor    | 0.03% 1kHz, 0.06% 10kHz                |
| Insulation Resistance | 100 GOhms                              |
| Max dV/dt             | 1000 V/us                              |
| Resistance            | 10.85 mOhms (100kHz)                   |
| Ripple Current        | 8.2 Amps (100kHz 85C), 220 Amps (Peak) |
| Inductance            | 18 nH                                  |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)