
## KEMET Part Number: SMR7.5182J50K01L16.5TR18

(F211KG182J050L)



SMR/F211, Film, Metallized PPS, General Purpose, 1800 pF, 5%, 50 VDC, 125°C, Lead Spacing = 7.5mm



General Information			
Series:	SMR/F211		
Dielectric:	Metallized PPS		
Style:	Radial		
Features:	Audio Applications		
RoHS:	Yes		
Lead:	Wire Leads		
AEC-Q200:	No		
Miscellaneous:	The rated voltage decreases 2% C between +125C and +150C.		
Notes:	Case Size = KG.		

Dimensions				
L	L 10mm -0.5mm			
Н	8mm -0.5mm			
Т	4mm -0.5mm			
S	7.5mm +/-0.4mm			
Н0	18.5mm +/-0.5mm			
F	0.6mm +/-0.05mm			
G	0.5mm NOM			

1700

**Packaging Quantity:** 

١	Е	0.6mm +/-0.05mm		romporataro rtangor	
ļ	г			Rated Temperature:	
	G	0.5mm NOM			
١				Dissipation Factor:	
				Insulation Resistance:	
ſ					
	Packaging Specifications			Max dV/dt:	_
-					
	Packagin	g:   T&R, 360mm			

Specifications				
Capacitance:	1800 pF			
Capacitance Tolerance:	5%			
Voltage AC:	30 VAC			
Voltage DC:	50 VDC			
Temperature Range:	-55/+150°C			
Rated Temperature:	125°C			
Dissipation Factor:	0.15% 1kHz, 0.25% 10kHz, 0.69 100kHz			
Insulation Resistance:	15 GOhms			
Max dV/dt:	30 V/us			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)