

**KEMET Part Number: R75MR4120JB30K**  
(75MR4120JB30K)

**KEMET**

a YAGEO company

R75, Film, Metallized Polypropylene, General Purpose, 1.2 uF, 10%, 400 VDC, 85°C, Lead Spacing = 27.5mm



General Information	
Series:	R75
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	Pulse
RoHS:	Yes
Lead:	Cut
AEC-Q200:	No
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.

Dimensions	
L	32mm +0.3/-0.7mm
H	20mm +0.1/-0.7mm
T	11mm +0.2/-0.7mm
S	27.5mm +/-0.4mm
LL	3.5mm +0.5mm
F	0.8mm +/-0.05mm

Specifications	
Capacitance:	1.2 uF
Capacitance Tolerance:	10%
Voltage AC:	220 VAC
Voltage DC:	400 VDC
Temperature Range:	-55/+105°C
Rated Temperature:	85°C
Dissipation Factor:	0.06% 1kHz
Insulation Resistance:	25 GOhms
Max dV/dt:	130 V/us
Resistance:	8.8 mOhms (100kHz)
Ripple Current:	6.93 Amps (100kHz 85C), 156 Amps (Peak)
Inductance:	18 nH

Packaging Specifications	
Packaging:	Tray
Packaging Quantity:	560

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

**KEMET**

a YAGEO company

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)