
KEMET Part Number: PEH532SCC3470M3



PEH532, Aluminum Electrolytic, 470 uF, 20%, 250 VDC, -40/+105°C



General Information		
Series:	PEH532	
Dielectric:	Aluminum Electrolytic	
Description:	Snap-In, Aluminum Electrolytic	
RoHS:	Yes	
Lead:	3 Pin Short	
AEC-Q200:	No	
Component Weight:	29 g	
Notes:	Add 0.5mm To D And 1mm To L For Sleeving.	
Shelf Life:	208 Weeks	

Dimensions	
D	30mm +/-0.5mm
L	30mm +/-1mm
S	10mm +/-0.1mm
LL	4mm +/-1mm
F	2mm +/-0.1mm

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	100

Specifications	
Capacitance:	470 uF
Capacitance Tolerance:	20%
Voltage DC:	250 VDC
Temperature Range:	-40/+105°C
Rated Temperature:	105°C
Life:	1500 Hrs (Rated Voltage And Ripple Current At 105C), 2000 Hrs (Rated Voltage At 105C)
Resistance:	250 mOhms (100Hz 20C), 120 mOhms (100kHz 20C)
Ripple Current:	1.2 Amps (100Hz 105C), 3.4 Amps (20kHz 40C)
Leakage Current:	352.5 uA (5min 20°C)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)