
KEMET Part Number: SMR7.5272K63K01L16.5TR18

(F211KG272K063L)



SMR/F211, Film, Metallized PPS, General Purpose, 2700 pF, 10%, 63 VDC, 125°C, Lead Spacing = 7.5mm



Series: SMR/F211 Dielectric: Metallized PPS Style: Radial Features: Audio Applications ROHS: Yes Lead: Wire Leads AEC-Q200: No
Style: Radial Features: Audio Applications RoHS: Yes Lead: Wire Leads
Features: Audio Applications RoHS: Yes Lead: Wire Leads
RoHS: Yes Lead: Wire Leads
Lead: Wire Leads
AEC-Q200: No
Miscellaneous: The rated voltage decreases 2% C between +125C and +150C.
Notes: Case Size = KG.

Dimensions	
L	10mm -0.5mm
Н	8mm -0.5mm
Т	4mm -0.5mm
S	7.5mm +/-0.4mm
Н0	18.5mm +/-0.5mm
F	0.6mm +/-0.05mm
G	0.5mm NOM

Dankarian O	18:	
Packaging Specifications		
Packaging:	T&R, 360mm	
Packaging Quantity:	1700	

Specifications		
Capacitance:	2700 pF	
Capacitance Tolerance:	10%	
Voltage AC:	40 VAC	
Voltage DC:	63 VDC	
Temperature Range:	-55/+150°C	
Rated Temperature:	125°C	
Dissipation Factor:	0.15% 1kHz, 0.25% 10kHz, 0.6% 100kHz	
Insulation Resistance:	15 GOhms	
Max dV/dt:	30 V/us	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)