

PHE426RB5100JR06

Aliases (F426BE103J1K6C, PHE426RB5100JB05R06)

PHE426/F426, Film, Metallized Polypropylene, General Purpose, 0.01 uF, 5%, 1600 VDC, 85°C, Lead Spacing = 15mm



Click [here](#) for the 3D model.

Dimensions

| | |
|----|---------------|
| L | 18mm MAX |
| H | 12.5mm MAX |
| T | 5.5mm MAX |
| S | 15mm +/-0.4mm |
| LL | 6mm NOM |
| F | 0.8mm NOM |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 1000 |

General Information

| | |
|------------------|--|
| Series | PHE426/F426 |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | Pulse |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Component Weight | 1.522 g |
| Notes | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

Specifications

| | |
|-----------------------|---------------------------|
| Capacitance | 0.01 uF |
| Capacitance Tolerance | 5% |
| Voltage AC | 650 VAC |
| Voltage DC | 1600 VDC, 1184 VDC (105C) |
| Temperature Range | -55/+105°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.05% 1kHz, 0.25% 100kHz |
| Insulation Resistance | 100 GOhms |
| Max dV/dt | 1500 V/us |
| Inductance | 6 nH |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)