

TCR08B823KWS

TCR Indust COG HT260C, Ceramic, 0.082 uF, 10%, 50 VDC, COG, Commercial, High Temperature, Lead Spacing = 10.16mm

Click here for the 3D model.

Dimensions	
L	12.7mm MAX
W	12.7mm MAX
Т	2.54mm MAX
S	10.16mm +/-0.76mm
LL	3.175mm MIN
F	0.635mm +/-0.051mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	1

General Information		
Series	TCR Indust COG HT260C	
Style	Radial	
Description	Commercial, High Temperature	
Features	Commercial	
RoHS	No	
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	2be24b5d-5233-4123-b41a-f759bcfae5fc	
Termination	Lead (SnPb)	
Failure Rate	N/A	
Testing and Reliability	Standard	
AEC-Q200	No	

Specifications			
Capacitance	0.082 uF		
Capacitance Tolerance	10%		
Voltage DC	50 VDC		
Dielectric Withstanding Voltage	125 VDC		
Temperature Range	-55/+260°C		
Temperature Coefficient	COG		
Dissipation Factor	0.15% 1 kHz 1.0Vrms		
Insulation Resistance	12.1951 GOhms		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)