

SIDE VIEW



TERMINAL END VIEW



Click [here](#) for the 3D model.

| Dimensions  |               |
|-------------|---------------|
| D           | 10mm +/-0.5mm |
| L           | 30mm +2mm     |
| S           | 5mm +/-0.5mm  |
| LL Negative | 15mm MIN      |
| LL Positive | 20mm MIN      |
| F           | 0.6mm NOM     |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 2000      |

### General Information

|             |   |
|-------------|---|
| Series      | ESW                                     |
| Dielectric  | Aluminum Electrolytic                   |
| Description | LowZ Single Ended Aluminum Electrolytic |
| Features    | Low Z                                   |
| RoHS        | Yes                                     |
| Lead        | Wire Leads                              |
| AEC-Q200    | No                                      |

### Specifications

|                         |                          |
|-------------------------|--------------------------|
| Capacitance             | 1,000 uF                 |
| Capacitance Tolerance   | 20%                      |
| Voltage DC              | 25 VDC, 32 VDC (Surge)   |
| Temperature Range       | -40/+105°C               |
| Rated Temperature       | 105°C                    |
| Life                    | 5000 Hrs                 |
| Dissipation Factor      | 14% 120Hz 20C            |
| Resistance              | 0.031 Ohms (100kHz 20C)  |
| Ripple Current          | 1910 mAmps (100kHz 105C) |
| Leakage Current         | 250 uA (2min 20°C)       |
| Impedance Ratio at -25C | 2                        |
| Impedance Ratio at -40C | 3                        |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)