



## ESH156M160AH2AA

ESH, Aluminum Electrolytic, 15 uF, 20%, 160 VDC, -25/+105°C, Lead Spacing = 5mm



## TERMINAL END VIEW



Click here for the 3D model.

Dimensions	
D	10mm +/-0.5mm
L	15mm +2mm
S	5mm +/-0.5mm
LL Negative	15mm MIN
LL Positive	20mm MIN
F	0.6mm NOM

## **Packaging Specifications**

Packaging	Bulk, Bag
Packaging Quantity	3000

General Information		
Series	ESH	
Dielectric	Aluminum Electrolytic	
Description	High CV Single Ended Aluminum Electrolytic	
Features	High CV	
RoHS	Yes	
Lead	Wire Leads	
AEC-Q200	No	

Specifications	
Capacitance	15 uF
Capacitance Tolerance	20%
Voltage DC	160 VDC, 200 VDC (Surge)
Temperature Range	-25/+105°C
Rated Temperature	105°C
Life	2000 Hrs
Dissipation Factor	15%
Ripple Current	90 mAmps (120Hz 105C)
Leakage Current	82 uA (2min 20°C)
Impedance Ratio at -25C	4

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)