

SIDE VIEW



TERMINAL END VIEW



Click [here](#) for the 3D model.

| Dimensions  |              |
|-------------|--------------|
| D           | 5mm +/-0.5mm |
| L           | 11mm +1.5mm  |
| S           | 2mm +/-0.5mm |
| LL Negative | 15mm MIN     |
| LL Positive | 20mm MIN     |
| F           | 0.5mm NOM    |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 10000     |

### General Information

|             |  |
|-------------|--|
| Series      | ESH  |
| Dielectric  | Aluminum Electrolytic                      |
| Description | High CV Single Ended Aluminum Electrolytic |
| Features    | High CV                                    |
| RoHS        | Yes  |
| Lead        | Wire Leads                                 |
| AEC-Q200    | No   |

### Specifications

|                         |                        |
|-------------------------|------------------------|
| Capacitance             | 33 uF                  |
| Capacitance Tolerance   | 20%                    |
| Voltage DC              | 25 VDC, 32 VDC (Surge) |
| Temperature Range       | -40/+105°C             |
| Rated Temperature       | 105°C                  |
| Life                    | 2000 Hrs               |
| Dissipation Factor      | 16% 120Hz 25C          |
| Ripple Current          | 75 mAmps (120Hz 105C)  |
| Leakage Current         | 8.25 uA (2min 20°C)    |
| Impedance Ratio at -25C | 2                      |
| Impedance Ratio at -40C | 3                      |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)